

(12) United States Patent Leidig et al.

(10) Patent No.:

US 9,638,358 B2

(45) Date of Patent:

May 2, 2017

(54) DUCT ELEMENT FOR THE EXHAUST SYSTEM OF A MOTOR VEHICLE

(71) Applicant: Witzenmann GmbH, Pforzheim (DE)

Inventors: Hans-Jurgen Leidig, Muhlacker (DE); Bernd Seeger, Pforzheim (DE)

Assignee: Witzenmann GmbH, Pforzheim (DE)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35

U.S.C. 154(b) by 377 days.

(21) Appl. No.: 14/173,887

Filed: Feb. 6, 2014 (22)

(65)**Prior Publication Data**

US 2014/0216590 A1 Aug. 7, 2014

(51) **Int. Cl.** F16L 11/14 (2006.01)(2006.01)F16L 11/15 F16L 55/033 (2006.01)F01N 13/16 (2010.01)

(52) U.S. Cl.

CPC F16L 11/14 (2013.01); F01N 13/16 (2013.01); F16L 11/15 (2013.01); F16L 55/0337 (2013.01); F01N 2530/02 (2013.01); F01N 2530/04 (2013.01)

(58) Field of Classification Search

See application file for complete search history.

(56)References Cited

U.S. PATENT DOCUMENTS

5,645,109 A * 7/1997 Herrero F16L 11/082 138/130

FOREIGN PATENT DOCUMENTS

102007060133 DE 6/2009 WO2012092931 WO 7/2012

* cited by examiner

Primary Examiner — Daniel J Schleis (74) Attorney, Agent, or Firm — Volpe and Koenig, P.C.

(57)**ABSTRACT**

A duct element for the exhaust system of a motor vehicle with an internal combustion engine, including at least one flexible duct part, preferably a bellows. The flexible duct part is embodied at least partially from a first type of steel with a Mo-content ≥4% or ≥6% and with a N-content from 0.3% to 0.6% or from 0.18% to 0.25%, preferably embodied from steel of the type 1.4565 or the type 1.4547. Furthermore a decoupling element is provided for motor vehicles with an internal combustion engine and a respective use of steel embodied with a Mo-content ≥4% or ≥6% and a N-content from 0.3% to 0.6% or from 0.18% to 0.25%, preferably steel of the type 1.4565 or 1.4547.

12 Claims, 1 Drawing Sheet

